



Focusing on Enhanced Performance

Product Name: KENZOL BRAKE FLUIDS (DOT 3 & DOT 4)

Application:

- KENZOL Brake Fluids is a high quality brake fluid blended from glycol esthers and polyglycols.
- Specially formulated to contain oxidation and corrosion inhibitors to enhance its chemical stability.
- Recommended for use in hydraulic brake and clutch applications in automobiles, motorcycles, light trucks and some bicycles.



Performance Benefits:

- Unique low moisture activity (LMA) formulation provides maximum wet boiling point protection against vapor lock brake failure when compared to other leading brake fluids in the market.
- Recommended for all anti-lock braking systems (ABS), hydraulic drum and disc braking systems and hydraulic clutches requiring DOT-3 & DOT-4 fluids.
- Provides superior fluidity at low temperatures for optimum braking response.
- Exceeds DOT-3 & DOT-4 and all leading auto manufacturer's requirements.
- Mixes with conventional brake fluid.

Performance Level: Recommended for the below performance levels / grades:

- SAE J1703, J1704, FMVSS No. 116 DOT 3 & 4 MOTOR VEHICLE BRAKE FLUID



Focusing on Enhanced Performance

Typical Properties: **KENZOL BRAKE FLUIDS (DOT 3 & DOT 4)**

Description	Test Method	DOT 3	DOT 4
Appearance	Visible	Transparent	Transparent
Equilibrium reflux boiling point(ERBP) °C	FMVSS 116	205 +	240 +
Wet Equilibrium reflux boiling point(WERBP) °C	FMVSS 116	140 +	155 +
Kinematic Viscosity @ 400C, cSt	ASTMD-445	1250	1100
pH	FMVSS 116	7.5 - 11	7.5 - 11.5
Flash point, ° C	ASTM D-92	130 +	121 +
Specific Gravity, 60 F	ASTM D-1298	1.07 - 1.15	1.07 - 1.15
Kinematic Viscosity @ -40C, cSt	ASTMD-445	740	800