



Focusing on Enhanced Performance

Product Name: KENZOL CVT Transmission Fluid

Application:

- KENZOL CVT Transmission fluid is a superior-performance fully-synthetic transmission fluid designed to meet the requirements of modern continuously variable transmissions (CVTs) of various Asian, North American and European designed vehicles.
- Specially developed for usage in all belt and chain CVTs to provide exceptional steel-on-steel frictional engagement to deliver maximum performance.
- Provides smooth and consistent all-weather step-less shifting to ensure a smooth driving experience.
- Excellent shear stability, low-temperature fluidity, and high wear protection helps extend transmission service life and protection of all transmission components.



Performance Benefits:

- Excellent Shear stability to prevent slipping of the belt.
- Outstanding metal-to-metal friction performance and torque transfer.
- Superior thermal and oxidation stability for consistent temperature performance.
- Anti-foam properties helps prevent fluid losses in severe service.
- Improved wet-clutch performance provides for less noise and a smooth driving experience.
- Longer drain capability compared to conventional products due to better oxidation resistance

Performance Level: Recommended for the below performance levels / grades:

- Audi/VW TL 52180, G 052 180, G 052 516
- BMW 8322 0136 376, 8322 0429 154, EZL 799A
- Daihatsu Amix CVTF-DC, CVTF-DFE
- Dodge/Jeep NS-2, CVTF+4®, MOPAR® CVT 4
- Ford CVT23, CVT30, WSS-M2C933-A
- GM/Saturn DEX CVT, CVTF I-Green2
- Honda HMMF, HCF-2
- Hyundai/Kia SP-CVT 1
- Mazda CVTF 3320
- Mercedes-Benz CVT28, 236.20
- Mini Cooper EZL 799A, ZF CVT V1
- Mitsubishi DiaQueen CVTF-J1, CVTF-J4
- Nissan NS-1, NS-2, NS-3
- Punch EZL 799A
- Shell Green IV
- Subaru e-CVTF, i-CVTF, Lineartronic® CVTF K0425Y0710
- Suzuki CVTF 3320, TC, NS-2, CVTF Green 1, CVTF Green 2
- Toyota/Lexus TC, FE



Focusing on Enhanced Performance

Typical Properties: **KENZOL CVT Transmission Fluid**

| Test | Method | CVT Fluid |
|------------------------|-------------|-----------|
| Color | ASTM D-1500 | Red |
| Density @15° C, gm/ml | ASTM D-1298 | 0.85 |
| Viscosity @100° C, cSt | ASTM D-445 | 7.2 |
| Viscosity @40° C, cSt | ASTM D-445 | 34 |
| Viscosity Index | ASTM D-2270 | 183 |
| Flash point COC, ° C | ASTM D-92 | 215+ |
| Pour point, ° C | ASTM D-97 | -48 |

