



Focusing on Enhanced Performance

**Product Name: KENZOL TRANSMAX Automatic Transmission Fluids**

**Application:**

- KENZOL TRANSMAX Automatic Transmission Fluids are formulated from solvent base oils, viscosity index improvers and special additives for the highest performance.
- It is designed for use in all passenger cars and commercial vehicles equipped with automatic transmission and hydraulic system where Type-A, DEX-II or DEX IV is recommended.
- Can be used in power steering systems, hydraulics and hydrostatic systems.



**Performance Benefits:**

- Excellent oxidation and friction stability, anti-wear properties, and low temperature fluidity desired for most transmission systems.
- Superior Extreme pressure and heat transfer properties.
- Wide range of seal compatibility.

**Performance Level:** Recommended for the below performance levels / grades:

**DEXRON II**

- GM Dexron IID
- MB 236.7; 236,5
- GM Type A Suffix A
- Ford ERS-M2C163-A
- Caterpillar TO-2
- MAN 339 V1, Z1
- Allison C-4
- Renk Doromat
- Hågglunds Denison HF-O
- VOITH TURBO H55.633539 (G607)
- ZF TE-ML-03D/04D/11A/14A/17C

**DEXRON III**

- General Motors Dexron IIIH
- General Motors Dexron IIIM
- GM Type A Suffix A
- Ford MERCON®
- MB 236.1, 236.5
- Allison C-4
- Voith H55.6335
- MAN 339 TYP Z1, V1
- ZF TE-ML-02F, 03D, 04D, 09, 11B, 14A, 17C
- CAT TO-2



Focusing on Enhanced Performance

## TYPE T-IV

- GM 9986195
- Land Rover LR002748 6-Speed Aisin F21
- Land Rover LR022460
- Matic K
- Mazda K020-W0-049
- Nissan 999MP-MTK00P - RE5F22A
- Toyota 00279-000T4
- Toyota 08886- 01705
- Toyota 08886-81016
- Toyota JWS 3309
- VOLVO 1161540
- VW/Audi G 055 025 A2
- BMW 83220402413 - MINI 6-Speed
- Aisin F21 - US / BMW 83227542290  
MINI 6-Speed Aisin F21
- ESSO JWS3317
- Fiat 9.55550-AV1
- Ford 1327936
- Ford WSSM2C924-A
- Ford XT-8QAW
- Opel/GM 1940771
- Opel/GM 1940774
- Renault 7711172225 - Getriebe SU0 / SU1
- Renault 7711218368 SU1 Gear
- Suzuki 99000-22800-001

Typical Properties: **KENZOL TRANSMAX Automatic Transmission Fluids**

### Lorem ipsum

SAE Grade	Method	Type A	DEX-II	DEX-III	Type IV
Appearance	Visual	Red	Red	Red	Red
Density @15° C, gm/ml	ASTM D-1298	0.87	0.86	0.85	0.851
Viscosity @100° C, cSt	ASTM D-445	7	7	7.1	7.1
Viscosity @40° C, cSt	ASTM D-445	42.7	39	34.8	37.9
Viscosity Index	ASTM D-2270	100	141	148	152
Flash point, COC, ° C	ASTM D-92	210	216	220	220
Pour point, ° C	ASTM D-97	-32	-36	-36	-40
Copper corrosion	ASTM D-130	1a	1a	1a	1a