



Focusing on Enhanced Performance

Product Name: KENZOL X-TREME 4T Motorcycle Engine Oil

Application:

- KENZOL X-TREME 4T Motorcycle Engine Oil is specially formulated with high viscosity index base oils and enriched with the latest additive technology, specially developed for new generation 4-Stroke gasoline engines.
- Meets and exceeds performance requirements for motorcycles of all leading manufacturers.
- Possesses special frictional properties required for smooth operation of wet clutches used in all types of two-wheelers and three-wheelers.



Performance Benefits:

- Reduced operating costs due to excellent wear protection for the engine parts and gears.
- Excellent starting in all seasons of the year.
- Splendid detergents keep the engine part clean.
- Sludge free oil environment in engine.
- Excellent resistance to foaming and corrosion.

Performance Level: Recommended for the below performance levels / grades:

- API-SL / JASO MA-2, API-SM, API-SG



Focusing on Enhanced Performance

Typical Properties: **KENZOL X-TREME 4T Motorcycle Engine Oil**

SAE Grade	Method	10W-30	10W-40	20W-40	20W-50
Appearance		Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Density @15° C, gm/ml	ASTM D-1298	0.868	0.872	0.876	0.88
Viscosity @100° C, cSt	ASTMD-445	10.12	14.25	14.85	18.51
Viscosity @40° C, cSt	ASTMD-445	69.5	109.25	115.25	164.5
Viscosity Index	ASTM D-2270	130	132	125	123
Flash point, COC, ° C	ASTM D-92	221	221	228	235
Pour point, ° C	ASTM D-97	-21	-21	-21	-21
Total Base Number	ASTM D-2896	7.5	7.5	7.3	7.1
Foaming Characteristic, ml (Mints)	ASTM D-892	0 / <10	0 / <10	0 / <10	0 / <10
		10 / <50	10 / <50	10 / <50	10 / <50
		0 / <10	0 / <10	0 / <10	0 / <10
Homogeneity & Miscibility	ASTM D-6922	pass	pass	pass	pass