



Focusing on Enhanced Performance

Product Name: KENZOL CALCIUM GREASE

DESCRIPTION

Kenzol calcium greases designed for the lubrication of spring leaves, handbrake cables, flexible drives and exposed chains. Suitable for use in slow speed plain bearings and slides where a heavy grease with solid lubricants is required. Use for plain bearing locks, latches, fasteners, cables, springs and as a fifth wheel lubricant. This grease can be used in industrial, mining and construction equipment including bulldozers, scrapers, loading shovels and dump trucks where graphite grease is recommended and high temperature capability is not required.

FEATURES

- Excellent water resistance.
- Good corrosion prevention.
- High mechanical stability.
- Good adhesivity.

TYPICAL CHARACTERISTICS

NLGI Grade	2	3
Color	Brown	Brown
Texture	Smooth	Smooth
Thickener Type	Calcium Soap	Calcium Soap
Drop Point, °C	128	130
Penetration, mm@ 25 , °C	275	235
Unworked		
Worked@ 60 strokes	280	240
Worked@ 10000 strokes	292	254
Base Oil Viscosity @40 °C, cSt	60	60
Copper-Corrosion	1	1
Water, m %	Max0.5	Max0.5
Oil Separation, 24 hr / 60 °C , wt %	2.6	2
Water wash out, 1hr @ 38 °C, wt %	<5	<5

HANDLING, HEALTH AND SAFETY

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use this product presents no particular toxic hazard. All lubricants and greases, of any kind should be handled with great care, particularly avoiding any prolonged contact with the skin.