



Focusing on Enhanced Performance

Product Name: KENZOL GREASE (MULTIPURPOSE 2 & 3)

DESCRIPTION

Kenzol MP Grease is a high quality, multipurpose. NLGI 2 and NLGI 3 grade, lithium hydroxy stearate grease based on an ISO VG 150 mineral oil. It is formulated to provide added protection against rusting and water washout in general purpose automotive applications at moderate temperatures and loads. Recommended for the lubrication of automotive chassis components, wheel bearings, clutch bearings, universal joints and ball joints of steering and suspension systems of passenger cars, trucks, farm tractors and most other types of mobile equipment operating under moderate conditions. The recommended operating temperature range of MP is -20°C to 120°C

FEATURES

- Excellent thermal and oxidation stability.
- Outstanding protection against rust and corrosion.
- Moderately high drop points and an excellent structural stability.
- Extended bearing life

PERFORMANCE LEVEL: Recommended for the below performance levels / grades:

- IS-14847:2000

TYPICAL CHARACTERISTICS

	MP-2	MP-3
Soap Type	Lithium	Lithium
Color	Amber /Yellow	Amber /Yellow
Texture	Smooth	Smooth
Work Penetration at 25 ° C	265-295	265-295
Drop Point ° C, Min.	180	180
Viscosity @40 ° C, cSt	150	150
Rust Protection Test, rating	pass	pass
Copper Corrosion 24h, 100C	18	18