



Focusing on Enhanced Performance

Product Name: **KENZOL CNG Motor Engine Oil**

Application:

- KENZOL CNG is a premium multi-grade lubricant specifically designed for use in compressed natural gas (CNG) engines.
- Specially formulated to provide reliable protection for trucks, buses, passenger cars and other commercial vehicles using Compressed Natural Gas (CNG).
- Advanced medium ash formulation provides excellent oxidation, nitration and thermal stability.

Performance Benefits:

- Shear stability reduces oil consumption.
- Low levels of Zinc and Phosphorus help extend converter life.
- Outstanding resistance to foaming and corrosion.
- Longer drain capability compared to conventional engine oils.

Typical Properties:

SAE Grade	Method	20W-40	20W-50	40
Appearance		Bright & Clear	Bright & Clear	Bright & Clear
Density @15°C, gm/ml	ASTM D-1298	0.882	0.882	0.882
Viscosity @100°C, cSt	ASTM D-445	15.19	19.77	14.5
Viscosity @40°C, cSt	ASTM D-445	120.9	191.3	142
Viscosity Index	ASTM D-2270	130	119	96
Flash point, COC, °C	ASTM D-92	220 +	230 +	220
Pour point, °C	ASTM D-97	-27	-24	-15