



Focusing on Enhanced Performance

**Product Name: KENZOL POWER Gasoline Engine Oils**

**Application:**

- KENZOL POWER is a unique engine lubricant specially formulated to meet the high performance requirements of the latest models of cars and trucks.
- It meets performance requirements of most European, Japanese, and American passenger car manufacturers.



**Performance Benefits:**

- Specially designed to control sludge formation ensuring a long life for engines.
- Excellent for all weather performance due to improved cold weather properties.
- Potential to double the oil drain intervals compared to current engine oils.
- Provides outstanding anti-wear, anti-oxidation, anti-foam, anti-rust and anti-corrosive properties.
- High engine cleanliness.

**Performance Level: Recommended for the below performance levels / grades:**

- API Service Category SM / CF, SL / CF
- ACEA A3 / B4-12
- MB 229.10/229.30
- VW 501 00 / 505 00



Focusing on Enhanced Performance

Typical Properties: **KENZOL POWER Gasoline Engine Oils**

SAE Grade	Method	10W-30	10W-40	15W-40	20W-50
Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Density @15° C, gm/ml	ASTM D-1298	0.871	0.875	0.88	0.88
Viscosity @100° C, cSt	ASTM D-445	10.75	14.80	15.10	19.05
Viscosity @40° C, cSt	ASTM D-445	74.8	117.25	122.15	176.25
Viscosity Index	ASTM D-2270	131	130	128	123
Flash point, COC, ° C	ASTM D-92	220	220	232	235
Pour point, ° C	ASTM D-97	-27	-27	-24	-15
Total Base Number	ASTM D-2896	7.5	7.5	7.5	7.5
Foaming Characteristic, ml (Mints)	ASTM D-892	0 / <10 10 / <50 0 / <10	0 / <10 10 / <50 0 / <10	0 / <10 10 / <50 0 / <10	0 / <10 10 / <50 0 / <10
Homogeneity & Miscibility	ASTM D-6922	pass	pass	pass	pass