



Focusing on Enhanced Performance

Product Name: KENZOL TURBO HD Diesel Engine Oils

Application:

- KENZOL TURBO HD is a highly advanced mono-grade lubricant designed for the demanding applications in all types of naturally aspirated and turbo charged engines.
- Suitable for both petrol and diesel engine specially developed for high output trucks, buses, passenger cars and vans.



Performance Benefits:

- Reduce engine scuffing and bore polishing.
- Excellent starting in all season of the year.
- Provides good oxidation stability.
- Splendid detergents keep the engine part clean.
- Sludge free oil environment in engine.

Performance Level: Recommended for the below performance levels / grades:

- API CF / SF, CD / SF, CF-4 / SF



Focusing on Enhanced Performance

Typical Properties: **KENZOL TURBO HD Diesel Engine Oils**

SAE Grade	Method	50	40
Appearance		Bright & Clear	Bright & Clear
Density @15° C, gm/ml	ASTM D-1298	0.88	0.87
Viscosity @100° C, cSt	ASTM D-445	18.8	15.5
Viscosity @40° C, cSt	ASTM D-445	215.1	162
Viscosity Index	ASTM D-2270	98	97
Flash point, COC, ° C	ASTM D-92	235	230
Pour point, ° C	ASTM D-97	-9	-9
Total Base Number	ASTM D-2896	8.5	8.5